



## Blastsafe – Metal zipper maintenance skills

1. When pulling the metal zipper, you must first bring the teeth on both sides close, the tops must be aligned, and then gently pull the metal zipper along the track, not too hard.
2. When moving the metal zipper head, be careful not to twist the placket or cloth edge into the metal zipper, so as not to cause "teeth crooked", "broken belly", "out of teeth" and other phenomena.
3. If the metal zipper is astringent and difficult to pull, don't pull it hard. You can apply wax or soap on the metal zipper to pull it.
4. If the single teeth of the metal zipper head are divergent and worn loose, you can use popular Shanjun pliers to gently clamp the closed end of the metal zipper head horizontally. The metal zipper will immediately become better, and the single teeth will be tight and no longer loose.
5. Prevent the metal zipper from being damp, oxidised, rusted and discoloured.
6. Avoid contact with humid environment: because metal zippers will become black due to metal oxidation and impregnation.
7. Avoid contact with rubber bands: because the rubber band itself contains sulphides, when the metal zipper is bundled with rubber bands, the metal chain teeth will be vulcanised (blackened).
8. Clean and dry in time after washing: because the dye or residual chemicals in the fabric undergo oxidation-reduction reactions with metal parts, it may cause discoloration of metal parts.

**We hope this can support our BLASTHEROES with information, to keep your safety products to last and keep you safe for longer.**

30.11.22

Jan Gaare CDO, Silencer AS